



cheek rest with integrated cartridge deflector

dust cover

adjustable iron rear sight

carrying handle with integrated STANAG 4694 rail

ambidextrous cocking handle

flip up front sight

VHS-D2

5 point adjustable buttstock

bolt catch release

magazine release

semi-transparent colored polymer 30 rd magazine

interchangeable magazine well

ambidextrous firing selector

lock texture handle

handguard with STANAG 4694 rail

bayonet mount with rifle grenade guide

muzzle flash suppressor

VHS-2

CAL 5,56 X 45



VHS-K2



VHS-D2,
VHS-BG



VHS-D2,
CT-1.5X



VHS-D2,
VHS-BG,
CT-1.5X

THE VHS FAMILY OF MILITARY ASSAULT RIFLES



HS Produkt

VHS-2

CAL 5,56 X 45

Technical specifications:

	Assault rifle VHS-D2	Assault rifle VHS-D2 CT - 1.5X	Assault rifle VHS-K2	Assault rifle VHS-K2 CT - 1.5X
1 Caliber:	5,56 x 45 mm	5,56 x 45 mm	5,56 x 45 mm	5,56 x 45 mm
2 Operating principle:	gas operated short stroke piston	gas operated short stroke piston	gas operated short stroke piston	gas operated short stroke piston
3 Barrel length:	500 mm	500 mm	410mm	410 mm
4 Rate of fire:	850 ± 100 rd/min	850 ± 100 rd/min	830 ± 100 rd/min	830 ± 100 rd/min
5 Muzzle velocity:	910 ± 30 m/sec	910 ± 30 m/sec	880 ± 30 m/sec	880 ± 30 m/sec
6 Length (overall):	800 mm	800 mm	710 mm	710 mm
7 Length (with extended buttstock):	850 mm	850 mm	760 mm	760 mm
8 Width:	75 mm	75 mm	75 mm	75 mm
9 Height with carrying handle:	234 mm	250 mm	234 mm	250 mm
10 Height with magazine (30 rd):	297 mm	312 mm	297 mm	312 mm
11 Weight without magazine:	3,9 kg	4,3 kg	3,75 kg	4,15 kg
12 Weight of empty magazine:	139 g	139 g	139 g	139 g

Optical sight with red dot and magnification CT-1.5X

1 Magnification
2 Diameter
3 Visible field
4 Optimal distance from eye
5 Operating temperature
6 Storage temperature

1.5 x ± 0,05
10 mm
5,1° ± 0,1°
70 ± 10 mm
from -32°C to +49°C
from -40°C to +71°C

1.5 x ± 0,05
10 mm
5,1° ± 0,1°
70 ± 10 mm
from -32°C to +49°C
from -40°C to +71°C



Special features:

- Ambidextrous: firing selector, cocking handle, bolt catch release and magazine release.
- Selectable left/right cartridge ejection port.
- Adjustable multiple aperture rear sight for 100m/200m, 300m, 400m and 500m.
- Interchangeable magazine well with M16 magazine option.

EXPECT THE BEST!

Technical specification	VHS-K2, 5,56×45 mm	VHS-D2, 5,56×45 mm	VHS-K2, 5,56×45 mm CT-1.5x	VHS-D2, 5.56×45 mm CT-1.5x
Caliber:	5.56×45 mm	5.56×45 mm	5.56×45 mm	5.56×45 mm
Ammunition:	5.56×45 mm; SS109	5.56×45 mm; SS109	5.56×45 mm; SS109	5.56×45 mm; SS109
Barrel length:	410 mm	500 mm	410 mm	500 mm
Velocity of firing:	830±100 rd./min.	850±100 rd./min	830±100 rd./min	850±100 rd./min
Muzzle velocity	880±30 m/sec	910±30 m/sec	880±30 m/sec	910±30 m/sec
Length (overall):	710 mm	800 mm	710 mm	800 mm
Length (drawn out buttstock):	760 mm	850 mm	760 mm	850 mm
Width:	75 mm	75 mm	75 mm	75 mm
Height with handle for carrying:	234 mm	234 mm	250 mm	250 mm
Height with magazine (30 rd) :	297 mm	297 mm	312 mm	312 mm
Weight without magazine:	3,75 kg	3,9 kg	4,15 kg	4,30 kg
Weight magazine (empty):	139 g	139 g	139 g	139 g